



MLFB-Ordering data: 1LE1603-2CA23-4AB4-Z
R11

Motor type: 1CV3252A

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U	Δ/Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _A /I _N	T _f /T _N	T _B /T _N	
400	Δ	50	55.00	- / -	95.00	2975	177.0	94.3	94.5	93.9	0.89	0.87	0.80	6.7	2.3	3.1	IE3
690	Y	50	55.00	- / -	55.00	2975	177.0	94.3	94.5	93.9	0.89	0.87	0.80	6.7	2.3	3.1	IE3
460	Δ	60	62.00	- / -	92.00	3575	166.0	93.6	93.6	92.7	0.90	0.88	0.82	6.7	2.3	3.0	IE3
460	Δ	60	55.00	- / -	83.00	3578	147.0	93.6	93.4	92.3	0.89	0.87	0.79	7.3	2.5	3.3	IE3
IM B3 / IM 1001			FS 250 M		385 kg	IP55	CC032A	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	73 dB(A)	76 dB(A)	Terminal box position	top
Moment of inertia	0.46 kg m²		Material of terminal box	cast iron
Bearing DE NDE	6315 C3	6315 C3	Type of terminal box	TB1 N01
Relubrication interval/quantity	25 g 25 g 4000 h		Contact screw thread	M10
Lubricants	Esso Unirex N3		Max. cross-sectional area	120.0 mm²
Regreasing device	Yes (standard)		Cable diameter from ... to ...	34.0 mm - 42.0 mm
Grease nipple	M10x1 DIN 3404 A		Cable entry	2xM63x1,5-2xM20x1,5
Type of bearing	Locating bearing NDE		Cable gland	4 plugs
Condensate drainage holes	Yes (standard)		Special design (1) R11 Terminal box rotated through 90°, cable entry from NDE	
External earthing terminal	Yes (standard)			
Vibration class	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	cast iron			
Data of anti condensation heating	-/-			
Coating (paint finish)	Special paint finish C3			
Color, paint shade	RAL7030			
Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m