



**Ordering data:** 1LE1001-0DC22-2AA4

**Motor type:** 1AV2082C

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	$\Delta$ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			$I_A/I_N$	$M_A/M_N$	$M_K/M_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	$I_A/I_N$	$T_A/T_N$	$T_B/T_N$	
230	$\Delta$	50	0.37	- / -	1.89	925	3.8	71.4	71.5	66.5	0.69	0.60	0.46	4.0	2.1	2.4	- / -
400	Y	50	0.37	- / -	1.09	925	3.8	71.4	71.5	66.5	0.69	0.60	0.46	4.0	2.1	2.4	- / -
460	Y	60	0.43	- / -	1.04	1125	3.7	75.3	75.3	72.3	0.69	0.60	0.46	4.2	2.1	2.6	- / -

IM B3 / IM 1001		FS 80 M	9 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	--	---------	------	------	--------------	------------------------

Mechanical data		Terminal box	
Sound pressure level 50 Hz/60Hz (load)	42 db(A)   45 db(A)	Terminal box position	top
Moment of inertia	0.0017 kg m <sup>2</sup>	Material of terminal box	Aluminium
Bearing DE   NDE	6004 2ZC3   6004 2ZC3	Type of terminal box	TB1 E00
Bearing lifetime	40000 h	Contact screw thread	M4
Lubricants	Esso Unirex N3	Max. cross-sectional area	1.5 mm <sup>2</sup>
Regreasing device	No	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Grease nipple	- / -	Cable entry	1xM25x1,5
Type of bearing	Preloaded bearing NDE	Cable gland	1 plugs
Condensate drainage holes	No	<b>Environmental conditions</b>	
External earthing terminal	No	Ambient temperature	-20 °C - +40 °C
Vibration class	A	Altitude above sea level	1000 m
Insulation	155(F) to 130(B)	<b>Special design</b>	
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	-/-		
Coating	Special paint finish		
Color	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		