



Ordering data: 1LE1002-1BA22-2KA4

Motor type: 1AV1112A

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U	Δ / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I/I _N	T _f /T _N	T _B /T _N	
230	Δ	50	4.00	- / -	14.10	2930	13.0	83.1	83.8	82.2	0.86	0.80	0.68	7.3	2.7	3.7	IE1
400	Y	50	4.00	- / -	8.10	2930	13.0	83.1	83.8	82.2	0.86	0.80	0.68	7.3	2.7	3.7	IE1
460	Y	60	4.55	- / -	7.70	3525	12.0	84.5	84.5	83.5	0.88	0.85	0.78	7.5	2.7	3.8	IE1

IM B14 / IM 3601		FS 112 M	25 kg	IP55	IEC/EN 60034-30-1:2014	IEC, DIN, ISO, VDE, EN		
------------------	--	----------	-------	------	------------------------	------------------------	--	--

Mechanical data		
Sound pressure level 50 Hz/60Hz (load)	69 db(A)	73 db(A)
Moment of inertia	0.0067 kg m²	
Bearing DE NDE	6206 2ZC3	6206 2ZC3
Bearing lifetime	40000 h	
Lubricants	Esso Unirex N3	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	Preloaded bearing NDE	
Condensate drainage holes	No	
External earthing terminal	No	
Vibration class	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	aluminum	
Data of anti condensation heating	-/-	
Coating	Standard paint finish C2	
Color	RAL7030	
Motor protection	(A) without (Standard)	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box	
Terminal box position	top
Material of terminal box	Aluminium
Type of terminal box	TB1 F00
Contact screw thread	M4
Max. cross-sectional area	4.0 mm²
Cable diameter from ... to ...	11.0 mm - 21.0 mm
Cable entry	2xM32x1,5
Cable gland	2 plugs
Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m
Special design	