

Data sheet for SIMOTICS S-1FK7



Figure similar

Ordering data 1FK7060-5AF71-1GH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Physical constants	
Rated speed	3000 rpm	Torque constant	1.33 Nm/A
Number of poles	8	Voltage constant at 20° C	84.5 V/1000*min ⁻¹
Rated torque (100 K)	4.7 Nm	Winding resistance at 20° C	1.44 Ω
Rated current	3.7 A	Rotating field inductance	14.7 mH
Static torque (60 K)	5.00 Nm	Electrical time constant	10.20 ms
Static torque (100 K)	6.0 Nm	Mechanical time constant	1.94 ms
Stall current (60 K)	3.7 A	Thermal time constant	30 min
Stall current (100 K)	4.5 A	Shaft torsional stiffness	42000 Nm/rad
Rotor moment of inertia	10.200 kgcm ²	Net weight of the motor	8.0 kg
Efficiency	90.0 %		

Mechanical data			
Motor type	Compact	Electrical connectors	Connectors for signals and power rotatable
Shaft height	63	Color of the housing	unpainted
Cooling	Natural cooling	Holding brake	with holding brake
Radial runout tolerance	0.040 mm	Shaft extension	Plain shaft
Concentricity tolerance	0.10 mm	Encoder system	Encoder AM32S/R: absolute encoder 32 S/R, 4096 revolutions multi-turn, with EnDat interface
Axial runout tolerance	0.10 mm		
Vibration severity grade	Grade A		
Connector size	1		
Degree of protection	IP64		
Design acc. to Code I	IM B5 (IM V1, IM V3)		
Temperature monitoring	KTY84 temperature sensor in the stator winding		



Figure similar

Ordering data 1FK7060-5AF71-1GH0

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	5 A
Optimum power	1.5 kW	Maximum inverter current	10 A
		Maximum torque	13.20 Nm