

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NU238NU2..EZylinderrollenlager

Cylindrical roller bearings

NU238-E-M1 (Series NU2..-E)

main dimensions to DIN 5412-1, non-locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	190 mm
D	340 mm
B	55 mm
D ₁	295 mm
D _a max	323 mm
d _a max	227 mm
d _a min	207 mm
d _b min	234 mm
E	306 mm
F	230 mm
r ₁ min	4 mm
r _{a1} max	3 mm
r _a max	3 mm
r _{min}	4 mm
s	4,7 mm Axial displacement facility from central position
m	22,8 kg Mass
C _r	680000 N Basic dynamic load rating, radial

C_{0r}	930000 N	Basic static load rating, radial
C_{ur}	81000 N	Fatigue limit load, radial
n_G	3050 1/min	Limiting speed
n_B	1720 1/min	Reference speed



