

Data sheet for SIMOTICS S-1FK7



Figure similar

Ordering data 1FK7105-5AF71-1FH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Physical constants	
Rated speed	3000 rpm	Torque constant	1.57 Nm/A
Number of poles	8	Voltage constant at 20° C	100.0 V/1000*min ⁻¹
Rated torque (100 K)	26.0 Nm	Winding resistance at 20° C	0.07 Ω
Rated current	18.0 A	Rotating field inductance	1.9 mH
Static torque (60 K)	40.00 Nm	Electrical time constant	26.00 ms
Static torque (100 K)	48.0 Nm	Mechanical time constant	1.40 ms
Stall current (60 K)	25.0 A	Thermal time constant	70 min
Stall current (100 K)	31.0 A	Shaft torsional stiffness	125000 Nm/rad
Rotor moment of inertia	169.000 kgcm ²	Net weight of the motor	41.5 kg
Efficiency	94.0 %		

Mechanical data			
Motor type	Compact	Electrical connectors	Connectors for signals and power rotatable
Shaft height	100	Color of the housing	unpainted
Cooling	Natural cooling	Holding brake	with holding brake
Radial runout tolerance	0.050 mm	Shaft extension	Plain shaft
Concentricity tolerance	0.10 mm	Encoder system	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Axial runout tolerance	0.10 mm		
Vibration severity grade	Grade A		
Connector size	1.5		
Degree of protection	IP64		
Design acc. to Code I	IM B5 (IM V1, IM V3)		
Temperature monitoring	KTY84 temperature sensor in the stator winding		



Figure similar

Ordering data 1FK7105-5AF71-1FH0

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	30 A
Optimum power	8.2 kW	Maximum inverter current	56 A
		Maximum torque	87.00 Nm