


3GVA062002-BSC

ABB contact for Netherlands



General Information

Product ID:	3GVA062002-BSC
ABB Type Designation:	M2VA 63B 4
Catalog Description:	No Description Available

Categories

Products » Motors and Generators » IEC Low Voltage AC Motors » Legacy IEC Low Voltage Motors » Aluminum Motors

Products » Motors and Generators » IEC Low Voltage AC Motors » Legacy IEC Low Voltage Motors » Marine General Purpose Motors

Additional Information

ABB Type Designation:	M2VA 63B 4
Altitude:	1000 m
Ambient Temperature:	40 °C
Bearing:	6202-2ZC3
Bearing NDE:	6201-2ZC3
Catalog Description:	No Description Available
Country of Origin:	Italy (IT) Romania (RO)
Customs Tariff Number:	85015220
Direction of Rotation:	Both sides

Electrical Data:

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	380-420 V	0.18 kW	1380 r/min	0.70 A	0.640	65.60 %	1.25 N·m	3.10
Y	--	60 Hz	440-480 V	0.22 kW	1650 r/min	1.20 A	0.680	65.60 %	1.25 N·m	3.10
D	--	50 Hz	220-240 V	0.18 kW	1380 r/min	0.70 A	0.640	65.60 %	1.25 N·m	3.10
D	--	60 Hz	250-280 V	0.22 kW	1650 r/min	1.20 A	0.680	65.60 %	1.25 N·m	3.10

Gross Weight:	4.76 kg
IC Class:	IC411
IM Class:	IMB5 IM3001
Insulation Class:	ICLF
IP Class:	IP55
Lubrication:	For life
Made To Order:	No
Minimum Order Quantity:	1 piece
Moment of Inertia:	0.00026 kg/m³
Poles (High):	4
Product Name:	3-Phase squirrel cage motor
Product Net Weight:	4.5 kg
Quote Only:	No
Replaced Product ID (OLD):	3GVA062002-BSAS 3GVA062002-BSA 3GAA062002-BSV
Selling Unit of Measure:	piece

10/23/2015	ABB ABB3GVA062002-BSC
Sound dB (A):	40 dB(A)
Standard:	IEC 60034-1
Starting of Motor:	Direct Online
Stocked At (Warehouses):	ITLCEXPU
Temperature Class Default:	--
Temperature Rise:	47 K
Terminator Box Location:	D-End top
Two Speed Motor:	No
Type of Duty:	S1
Voltage Code:	S

