

Data sheet for three-phase Squirrel-Cage-Motors



Ordering data : 1LA9083-4KA17

without (standard)

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data:

Rated motor voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	0.75 kW		0.86 kW			
Rated motor speed :	1400 1/ min		1700 1/ min			
Rated motor torque :	5.1 Nm		4.8 Nm			
Rated motor current (IE) :	VD	VY		VY		
	3.15 A	1.81 A		1.72 A		
Starting / rated motor current :	5.8		6.7			
Breakdown / rated motor	3.5		3.4			
Starting / rated motor torque :	4.0		3.5			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	79.6%	79.6%	87.6%	82.5%	82.5%	81.5%
Power factor :	0.75	0.69	0.56	0.76	0.70	0.58
Efficiency class :	IE2		IE2			

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	47 dB(A)	51 dB(A)
Moment of inertia :	0.0024 kg*m ²	
Bearing DE :	6004 2ZC3	
Bearing NDE :	6004 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	080 M
Type of construction :	(7) IM B34 / IM 2101, standard flange
Weight in kg, without optional accessories :	12.30 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 030
Contact screw thread :	M4
Max. cross-sectional area :	1.50 mm ²
Cable diameter from ... to ... :	9.00 mm - 17.00 mm
Cable entry :	1xM25x1,5-1xM16x1,5
Cable gland :	2 plugs

Special design: