

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP2309-ENUP23..-EZylinderrollenlager

Cylindrical roller bearings

NUP2309-E-XL-TVP2 (Series NUP23..-E)

main dimensions to DIN 5412-1, locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	45 mm
D	100 mm
B	36 mm
B ₃	6 mm
D ₁	84,1 mm
d ₁	64,4 mm
D _a max	91 mm
d _a min	54 mm
d _c min	66 mm
E	88,5 mm
F	58,5 mm
r ₁ min	1,5 mm
r _a max	1,5 mm
r _{min}	1,5 mm
m	1,36 kg Mass
C _r	163000 N Basic dynamic load rating, radial
C _{0r}	154000 N Basic static load rating, radial

Cur	28000 N	Fatigue limit load, radial
nc	8500 1/min	Limiting speed
nb	5200 1/min	Reference speed



